NSN 5910-00-139-9998



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-139-9998 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.125 inches **Body Length:** 0.930 inches **Body Width:** 0.312 inches **Body Height:** 0.100 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.697 inches and 0.703 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 4700.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -190.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -5.00 to 5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0100 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-00-139-9998

Plastic Dielectric Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A010b0