

View Online at <https://aerobasegroup.com/nsn/5910-00-140-6266>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.310 inches

Body Length:

0.340 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware

Capacitance Value Per Section:

100.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-85.0 to 22.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.0000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0