NSN 5910-00-146-4184

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-146-4184

Body	Stv	-ما
DUUV	OLV.	ıc.

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 0.063 inches and 0.094 inches

Body Length:

Between 0.410 inches and 0.430 inches

Body Width:

Between 0.150 inches and 0.170 inches

Body Height:

Between 0.320 inches and 0.340 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.290 inches and 0.310 inches

Terminal Diameter:

0.063 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

4.700 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

50.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-00-146-4184

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



em			

No

Fiig:

A010b0