## NSN 5910-00-147-6851

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-147-6851 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.185 inches and 0.215 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 22.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -56.0 to 22.0 without voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Power Factor At Reference Tempurature In Percent:** 2.5000 **Terminal Surface Treatment:** Solder **Test Data Document:** 96214-532104 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5910-00-147-6851

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



em			

No

Fiig:

A010b0