

View Online at https://aerobasegroup.com/nsn/5910-00-148-8883

| Body Style:   |            |
|---|------------|
| Chip type   |            |
| Reliability Indicator:  |            |
| Not established   |            |
| Body Length:  |            |
| 0.370 inches  |            |
| Body Width:   |            |
| 0.115 inches  |            |
| Body Height:  |            |
| 0.070 inches  |            |
| Schematic Diagram Designator:                                     |            |
| No common or grounded electrode (s)                               |            |
| Capacitance Value Per Section:                                    |            |
| 0.100 microfarads single section                                  |            |
| Nonderated Operating Temp:  |            |
| Between -55.0 degrees celsius and 125.0 degrees celsius           |            |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per De  | g Celsius: |
| 0.0 single section  |            |
| Nonderated Continuous Voltage Rating And Type Per Section:        |            |
| 100.0 dc single section   |            |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg 0 | Celsius:   |
| -15.0/+15.0 single section  |            |
| Tolerance Range Per Section:                                      |            |
| -10.00/+10.00 percent single section                              |            |
| Case Material:  |            |
| Ceramic   |            |
| Insulation Resistance At Reference Temp:                          |            |
| 100000.0 megohms  |            |
| Terminal Surface Treatment:                                       |            |
| Solder  |            |
| Terminal Type And Quantity:                                       |            |
| 2 bonding pad   |            |
| Shelf Life:   |            |
| N/a   |            |
| Unit Of Measure:  |            |
| -   |            |
| Demilitarization:   |            |
| No  |            |
| Fiig:   |            |
| A010b0  |            |