NSN 5910-00-150-0234

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-150-0234

Body Style: W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.265 inches **Body Width:** 0.135 inches **Body Height:** 0.095 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.140 inches and 0.202 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 100.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -0.0 to 70.0 single section **Tolerance Range Per Section:** -2.00 to 2.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.0007 **Terminal Surface Treatment:** Solder **Test Data Document:**

98738-21+231000 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

NSN 5910-00-150-0234

Mica Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0