

View Online at <https://aerobasegroup.com/nsn/5910-00-150-1201>

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

Between 2.200 inches and 2.300 inches

Body Width:

Between 1.560 inches and 1.700 inches

Body Height:

2.875 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

18.0

Highest Frequency At Which Rf Current Rating Applies In Kilohertz:

3000.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

12.0

Lowest Frequency At Which Rf Current Rating Applies In Kilohertz:

100.0

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 ac-peak single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0