Mica Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-150-1202

# **Body Style:**

W/thd mtg hole, terminal (s) on one end

### **Reliability Indicator:**

Not established

# **Body Diameter:**

2.000 inches

### **Body Length:**

2.000 inches

### **Unthreaded Mounting Hole Diameter:**

0.250 inches

### Center To Center Distance Between Mounting Facilities Parallel To Diameter:

3.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

### Mounting Facility Type And Quantity:

### 2 unthreaded mounting holes

**Features Provided:** 

Mounting hardware

# Capacitance Value Per Section:

6000.000 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

4000.0 ac-peak single section

# Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-50.0 to 100.0 single section

#### **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

#### **Case Material:**

Plastic

# Insulation Resistance At Reference Temp:

7500.0 megohms

# **Terminal Type And Quantity:**

1 threaded hole

Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

No

# Fiig:

A010b0