

View Online at <https://aerobasegroup.com/nsn/5910-00-150-4524>

**Body Style:**

W/mtg flanges, terminals on opposite ends

**Reliability Indicator:**

Not established

**Body Diameter:**

5.000 inches

**Body Length:**

5.750 inches

**Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:**

15.0

**Highest Frequency At Which Rf Current Rating Applies In Kilohertz:**

3000.0

**Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:**

4.3

**Lowest Frequency At Which Rf Current Rating Applies In Kilohertz:**

100.0

**Unthreaded Mounting Hole Diameter:**

0.380 inches

**Center To Center Distance Between Mounting Facilities Parallel To Diameter:**

5.750 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Insulation Resistance At Maximum Operating Temp:**

2000.0 megohms

**Capacitance Value Per Section:**

680.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 70.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

30000.0 ac-peak single section

**Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:**

+0.0 to 70.0 single section

**Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

7500.0 megohms

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0