## NSN 5910-00-150-4673



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-150-4673 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.230 inches **Body Width:** 0.310 inches **Body Height:** 0.130 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.175 inches and 0.225 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 33.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 30.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 10.0 dc single section **Tolerance Range Per Section:** -20.00 to 20.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum** 

Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
0.0600
Dc Leakage At Reference Temp:
3.000 microamperes
Terminal Surface Treatment:
Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-150-4673

Electrolytic Fixed Capacitor - Page 2 of 2



| She  | lf | Life: |  |
|------|----|-------|--|
| Oile | •• | LIIV. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0