

View Online at https://aerobasegroup.com/nsn/5910-00-152-8255

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.432 inches

**Body Length:** 

1.187 inches

**Terminal Diameter:** 

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

6000.0 megohms

## Capacitance Value Per Section:

1.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

50000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

### **Terminal Surface Treatment:**

Solder

### **Case Insulation Material:**

Plastic

### **Test Data Document:**

81349-mil-c-39022 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead



**Specification Data:** 

81349-mil-c-39022/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0