NSN 5910-00-152-8932

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-152-8932

View Online at https://aerobasegroup.com/nsn/5910-00-152-8932
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.450 inches
Body Width:
0.360 inches
Body Height:
0.170 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.203 inches and 0.265 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
20000.0 megohms
Capacitance Value Per Section:
39.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:
-20.0 to 100.0 single section
Tolerance Range Per Section:
-0.50 to 0.50 picofarads single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
100000.0 megohms
Quality Factor At Reference Temp:
1000.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5910-00-152-8932

Mica Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0