Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-152-9568

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

N-2

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.332 inches

Body Length:

0.813 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

1000.0 megohm-microfarads

Capacitance Value Per Section:

0.470 microfarads single section

Nonderated Operating Temp:

Between -62.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-0.50/+0.50 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

300000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.2000

Terminal Surface Treatment:

Gold

Case Insulation Material:

Plastic

Precious Material And Location:

Terminal surface gold

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0