NSN 5910-00-153-4460

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-153-4460 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.546 inches **Body Length:** 2.828 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 300.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 135.00 Dc Leakage At Reference Temp: 60.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-153-4460

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | | |
|----|----|----|-----|------|--|
| C. | ~~ | 14 | I i | ife: | |
| J. | 16 | | | HE. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0