

View Online at <https://aerobasegroup.com/nsn/5910-00-160-6753>

**Body Style:**

Rotary

**Body Length:**

1.297 inches

**Body Width:**

0.875 inches

**Body Height:**

Between 0.297 inches and 0.406 inches

**Unthreaded Mounting Hole Diameter:**

0.145 inches and 0.145 inches

**Dissipation Factor At 25 Deg Celsius In Percent:**

0.2

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.625 inches

**Individual Section Quantity:**

2

**Inclosure Type:**

Encapsulated

**Adjustment Device Rotation:**

360.0 degrees clockwise

**Adjustment Device Torque:**

Between 4.000 inch-ounces and 24.000 inch-ounces

**Insulation Dc Resistance At Max Operating Temp:**

10000.0 megohms

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:**

+4.5 to 20.0 all sections

**Nonderated Voltage Rating And Type:**

500.0 dc continuous all sections

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

-4.50 to 2.00 and -2.50 to 2.00 all sections

**Adjustment Device Drive Type And Quantity:**

2 slotted screw

**Capacitance Drift In Picofarads:**

0.50 all sections

**Special Features:**

Mtg holes offset 0.156 in.C to c along lg

**Material:**

Ceramic base

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0