

View Online at <https://aerobasegroup.com/nsn/5910-00-160-6753>

Body Style:

Rotary

Body Length:

1.297 inches

Body Width:

0.875 inches

Body Height:

Between 0.297 inches and 0.406 inches

Unthreaded Mounting Hole Diameter:

0.145 inches and 0.145 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.2

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Individual Section Quantity:

2

Inclosure Type:

Encapsulated

Adjustment Device Rotation:

360.0 degrees clockwise

Adjustment Device Torque:

Between 4.000 inch-ounces and 24.000 inch-ounces

Insulation Dc Resistance At Max Operating Temp:

10000.0 megohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+4.5 to 20.0 all sections

Nonderated Voltage Rating And Type:

500.0 dc continuous all sections

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50 to 2.00 and -2.50 to 2.00 all sections

Adjustment Device Drive Type And Quantity:

2 slotted screw

Capacitance Drift In Picofarads:

0.50 all sections

Special Features:

Mtg holes offset 0.156 in.C to c along lg

Material:

Ceramic base

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0