

View Online at <https://aerobasegroup.com/nsn/5910-00-160-6755>

Body Style:

Rotary

Body Length:

1.300 inches

Body Width:

0.880 inches

Body Height:

0.406 inches

Unthreaded Mounting Hole Diameter:

0.145 inches and 0.145 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.2

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.625 inches

Individual Section Quantity:

2

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 4.000 inch-ounces and 24.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10.0 gigohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+1.5 to 7.0 all sections

Nonderated Voltage Rating And Type:

500.0 dc continuous all sections

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50 to 2.00 and -2.50 to 2.00 all sections

Adjustment Device Drive Type And Quantity:

2 slotted screw

Capacitance Drift In Picofarads:

0.50 all sections

Test Data Document:

81349-mil-c-81 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0