

View Online at <https://aerobasegroup.com/nsn/5910-00-165-2762>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surfacew/thd mtg hole(s)/stud(s) terminal(s) on one surfacew/thd mtg hole(s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

0.180 inches 0.180 inches 0.180 inches

Body Length:

0.875 inches

Body Width:

0.875 inches

Body Height:

1.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

560.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0