

View Online at <https://aerobasegroup.com/nsn/5910-00-165-2826>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:**

Not establishednot establishednot establishednot established

**Terminal Length:**

1.500 inches 1.500 inches 1.500 inches 1.500 inches

**Body Diameter:**

0.289 inches

**Body Length:**

0.722 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

47.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

330.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

35.0 dc single section

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

6.0000

**Dc Leakage At Reference Temp:**

41.300 microamperes

**Terminal Surface Treatment:**

Gold

**Case Insulation Material:**

Plastic

**Precious Material And Location:**

Terminals gold

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0