

View Online at <https://aerobasegroup.com/nsn/5910-00-165-2832>

**Body Style:**

W/thd bushing mtg, terminal (s) on one endw/thd bushing mtg, terminal(s) on one endw/thd bushing mtg, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

0.215 inches 0.215 inches 0.215 inches

**Body Diameter:**

0.875 inches

**Body Length:**

0.688 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Anode Type:**

Solid

**Impedance At Minimum Operating Tempurature In Ohms:**

50.0

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

80.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.500 inches

**Dc Leakage At Maximum Operating Temp:**

180.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

60.0 dc single section

**Tolerance Range Per Section:**

-15.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Equivalent Series Resistance At Reference Tempurature In Ohms:**

2.70

**Dc Leakage At Reference Temp:**

65.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

1 uninsulated wire lead and 1 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0