

View Online at <https://aerobasegroup.com/nsn/5910-00-166-3182>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

2.250 inches 2.250 inches 2.250 inches

**Body Diameter:**

0.296 inches

**Body Length:**

0.703 inches

**Terminal Diameter:**

0.025 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

30.0

**Electrical Polarization:**

Polarized

**End Application:**

Oliver perry class ffg; wasp class lhd; sturgeon class ssn (637); los angeles class ssn (688); nimitz class cvn; kidd class ddg; forrestal class cv; virginia class cgn (41); spruance class dd (963)

**Capacitance Value Per Section:**

220.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

7.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

8.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Tantalum

**Equivalent Series Resistance At Reference Temperature In Ohms:**

3.00

**Dc Leakage At Reference Temp:**

1.000 microamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0