

View Online at <https://aerobasegroup.com/nsn/5910-00-166-9888>

**Body Style:**

Rotary

**Body Length:**

0.854 inches

**Body Width:**

0.656 inches

**Body Height:**

0.375 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

-1500.0 single section

**Unthreaded Mounting Hole Diameter:**

0.120 inches and 0.120 inches

**Quality Factor At 25 Deg Celsius:**

400.0

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.437 inches

**Inclosure Type:**

Encased

**Adjustment Device Torque:**

Between 4.000 inch-ounces and 20.000 inch-ounces

**Insulation Dc Resistance At 25 Deg Celsius:**

10.0 gigohms

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Capacitance Range In Picofarads:**

+11.0 to 110.0 single section

**Nonderated Voltage Rating And Type:**

500.0 dc continuous single section

**Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:**

+6.00 to 16.00 and -15.00/-9.00 single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Capacitance Drift In Picofarads:**

0.50 single section

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A096a0