## NSN 5910-00-166-9888

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-166-9888 **Body Style:** Rotary **Body Length:** 0.854 inches **Body Width:** 0.656 inches **Body Height:** 0.375 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -1500.0 single section **Unthreaded Mounting Hole Diameter:** 0.120 inches and 0.120 inches **Quality Factor At 25 Deg Celsius:** 400.0 Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.437 inches **Inclosure Type: Encased Adjustment Device Torque:** Between 4.000 inch-ounces and 20.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 2 unthreaded hole **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +11.0 to 110.0 single section **Nonderated Voltage Rating And Type:** 500.0 dc continuous single section Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: +6.00 to 16.00 and -15.00/-9.00 single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Capacitance Drift In Picofarads: 0.50 single section **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5910-00-166-9888

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0