NSN 5910-00-168-3321



Ceramic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-168-3321 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.500 inches **Body Width:** 0.500 inches **Body Height:** 0.150 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.385 inches and 0.415 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohms **Capacitance Value Per Section:** 330.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -150.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -15.0/+15.0 single section **Tolerance Range Per Section:** -2.00 to 2.00 percent single section Case Material: **Plastic Insulation Resistance At Reference Temp:** 50000.0 megohms **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-00-168-3321

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0