## NSN 5910-00-168-3384

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-168-3384 **Body Style:** Cylindrical **Overall Length:** 0.547 inches **Terminal Length:** 0.094 inches **Overall Diameter:** 0.075 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 50.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Terminal Diameter:** 0.075 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Inclosure Type: Encased Adjustment Device Torque:** Between 0.100 inch-ounces and 1.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -65.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.1/+1.3 single section **Nonderated Voltage Rating And Type:** 500.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Capacitance Drift In Picofarads:** 0.01 single section **Precious Material And Location:** Metal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 2 ferrule Shelf Life:

N/a

## NSN 5910-00-168-3384

Glass Dielectric Variable Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A096a0