

View Online at https://aerobasegroup.com/nsn/5910-00-168-3384

New Online at https://aeiobasegroup.com/nsi//3910-00-106-3364	
Body Style:	
Cylindrical	
Overall Length:	
0.547 inches	
Terminal Length:	
0.094 inches	
Overall Diameter:	
0.075 inches	
Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:	
50.0 single section	
Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:	
-50.0/+50.0 single section	
Terminal Diameter:	
0.075 inches	
Quality Factor At 25 Deg Celsius:	
500.0	
Inclosure Type:	
Encased	
Adjustment Device Torque:	
Between 0.100 inch-ounces and 1.000 inch-ounces	
Insulation Dc Resistance At 25 Deg Celsius:	
10.0 gigohms	
Mounting Facility Type And Quantity:	
2 terminal	
Nonderated Operating Temp:	
Between -65.0 degrees celsius and 125.0 degrees celsius	
Capacitance Range In Picofarads:	
+0.1/+1.3 single section	
Nonderated Voltage Rating And Type:	
500.0 dc continuous single section	
Adjustment Device Drive Type And Quantity:	
1 slotted screw	
Capacitance Drift In Picofarads:	
0.01 single section	
Precious Material And Location:	
Metal surfaces gold	
Precious Material:	
Gold	
Terminal Type And Quantity:	
2 ferrule	
Shelf Life:	
N/a	



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A096a0