Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-169-8977

#### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

#### **Terminal Length:**

2.250 inches

#### **Body Diameter:**

0.406 inches

#### **Body Length:**

0.766 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Anode Type:

Solid

#### Impedance At Minimum Operating Tempurature In Ohms:

35.0

## Electrical Polarization:

Polarized

## Features Provided:

Hermetically sealed case

#### Capacitance Value Per Section:

150.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Dc Leakage At Maximum Operating Temp:

18.0 milliamperes

#### Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

#### **Tolerance Range Per Section:**

-20.00 to 20.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Tantalum

## Power Factor At Reference Tempurature In Percent:

41.5000

## Dc Leakage At Reference Temp:

2.000 microamperes

# **Terminal Surface Treatment:**

Solder

## Case Insulation Material:

Plastic

# NSN 5910-00-169-8977

Electrolytic Fixed Capacitor - Page 2 of 2



#### **Test Data Document:**

89110-3-26357 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A010b0