NSN 5910-00-169-9329

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-169-9329 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.620 inches **Body Length:** 0.800 inches **Body Width:** 0.411 inches **Body Height:** 0.178 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.695 inches and 0.705 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 500.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Criticality Code Justification:** Feat **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 250000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Special Features:** Item must comply with requirements of desc production standard no. L00609 **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

N/a

NSN 5910-00-169-9329

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0