## NSN 5910-00-170-8119

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-170-8119 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.250 inches **Body Length:** 0.531 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.230 inches **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 32 **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches Capacitance Range In Picofarads: +0.8/+10.0 single section **Nonderated Voltage Rating And Type:** 750.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 

1 slotted screw

**Capacitance Drift In Picofarads:** 

0.02 single section

## NSN 5910-00-170-8119

Glass Dielectric Variable Capacitor - Page 2 of 2



## **Test Data Document:**

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal	Type A	And G	Quantity:
----------	--------	-------	-----------

	lead

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A096a0