NSN 5910-00-170-9557



Air Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-170-9557 **Body Style:** Piston **Overall Length:** 0.562 inches **Terminal Length:** 0.406 inches **Body Length:** 0.406 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -20.0 to 20.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.203 inches **Terminal Diameter:** 0.062 inches **Quality Factor At 25 Deg Celsius:** 2000.0 **Fragility Factor:** Moderately rugged **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.015 inches **Inclosure Type:** Encased **Terminal Location:** One side perpendicular **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Rotation:**

7.0 turns clockwise and 7.0 turns counterclockwise

Adjustment Device Torque:

Between 1.000 inch-ounces and 5.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

NSN 5910-00-170-9557

Air Dielectric Variable Capacitor - Page 2 of 2



Capacitance Range In Picofarads:
+1.0/+10.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.10 single section
Material:
Steatite base
Precious Material And Location:
Metal surfaces gold and metal surfaces silver
Precious Material:
Gold and silver
Terminal Type And Quantity:
1 pin and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A096a0