NSN 5910-00-170-9559

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-170-9559 |
|---|
| Body Style: |
| Rotary |
| Body Diameter: |
| 0.276 inches |
| Body Height: |
| 0.315 inches |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| -550.0 single section |
| Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius: |
| -250.0 to 250.0 single section |
| Center To Center Distance Between Terminals Parallel To Diameter: |
| 0.224 inches |
| Inclosure Type: |
| Encased |
| Insulation Dc Resistance At 25 Deg Celsius: |
| 10000.0 megohms |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Capacitance Range In Picofarads: |
| +3.2 to 18.0 single section |
| Nonderated Voltage Rating And Type: |
| 250.0 dc continuous single section |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A096a0 |
| |