## NSN 5910-00-174-6994

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-174-6994

## Body Style:

W/o mtg facilities, axial terminals

## Mil-std-1276 Wire Lead Type Designator:

N-2

#### **Reliability Indicator:**

Established

#### **Terminal Length:**

1.625 inches

#### **Body Diameter:**

Between 0.235 inches and 0.255 inches

#### **Body Length:**

0.687 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Features Provided:**

Hermetically sealed case

### Capacitance Value Per Section:

0.150 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-1.00 to 1.00 percent single section

#### **Case Material:**

Metal

#### Dissipation Factor At Reference Tempurature In Percent:

0.2500

**Terminal Surface Treatment:** 

Solder

## Case Insulation Material:

Plastic

## Test Data Document:

81349-mil-c-39022/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-174-6994

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

