

View Online at <https://aerobasegroup.com/nsn/5910-00-174-9953>

**Body Style:**

W/thd bushing mtg, terminal (s) on one end

**Reliability Indicator:**

Not established

**Terminal Length:**

0.500 inches

**Body Diameter:**

1.500 inches

**Body Length:**

4.500 inches

**Body Width:**

1.500 inches

**Body Height:**

1.500 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.188 inches

**Terminal Diameter:**

0.190 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Internal Electrical Connection Type:**

Inserted tab

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

15.0 megohm-microfarads

**Capacitance Value Per Section:**

4.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.750 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

600.0 dc single section

**Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

1500.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:**

1.0000

**Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349-mil-c-25/3b government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0