

View Online at https://aerobasegroup.com/nsn/5910-00-175-3800

Plastic Dielectric Fixed Capacitor - Page 1 of 2

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Not established

## **Terminal Length:**

1.125 inches

## Body Length:

0.930 inches

#### **Body Width:**

0.312 inches

#### **Body Height:**

0.100 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.700 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000000.0 megohms

#### Capacitance Value Per Section:

1500.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-190.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-0.50 to 0.50 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

10000000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.0200

## **Terminal Surface Treatment:**

Solder

## **Terminal Type And Quantity:**

2 uninsulated wire lead

#### Shelf Life:

N/a

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0