Glass Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-175-4924

Reliability Indicator:Not establishedTerminal Length:1.125 inchesBody Length:0.391 inchesBody Height:0.203 inchesFeatures Provided:Hermetically sealed caseCapacitance Value Per Section:16.000 picofarads single sectionNonderated Operating Temp:Unable to decode and 85.0 degrees celsiusTempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:0.0 single section
Terminal Length:1.125 inchesBody Length:0.391 inchesBody Height:0.203 inchesFeatures Provided:Hermetically sealed caseCapacitance Value Per Section:16.000 picofarads single sectionNonderated Operating Temp:Unable to decode and 85.0 degrees celsiusTempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
 1.125 inches Body Length: 0.391 inches Body Height: 0.203 inches Features Provided: Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Body Length:0.391 inchesBody Height:0.203 inchesFeatures Provided:Hermetically sealed caseCapacitance Value Per Section:16.000 picofarads single sectionNonderated Operating Temp:Unable to decode and 85.0 degrees celsiusTempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
 0.391 inches Body Height: 0.203 inches Features Provided: Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Body Height: 0.203 inches Features Provided: Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.203 inches Features Provided: Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Features Provided: Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Hermetically sealed case Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Capacitance Value Per Section: 16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
16.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-25.0 to 25.0 single section
Case Material:
Glass
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A010b0