## NSN 5910-00-175-7848

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-175-7848 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.550 inches **Body Length:** 2.940 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 25.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 500.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section **Tolerance Range Per Section:** -15.00 to 15.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent:** 6.0000 Dc Leakage At Reference Temp: 100.000 microamperes **Case Insulation Material:** 

**Plastic Terminal Type And Quantity:** 2 uninsulated wire lead

## NSN 5910-00-175-7848

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0