

View Online at <https://aerobasegroup.com/nsn/5910-00-176-7207>

**Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:**

Not establishednot establishednot establishednot established

**Terminal Length:**

Between 1.250 inches and 1.250 inches and 1.250 inches and 1.250 inches and 1.750 inches 1.750 inches 1.750 inches 1.750 inches

**Body Diameter:**

0.145 inches 0.145 inches

**Body Length:**

0.600 inches 0.600 inches

**Terminal Diameter:**

Between 0.019 inches and 0.019 inches and 0.021 inches 0.021 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)no common or grounded electrode(s)

**Anode Type:**

Solidsolid

**Electrical Polarization:**

Polarizedpolarized

**Capacitance Value Per Section:**

30.000 microfarads single section30.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and -55.0 degrees celsius and 85.0 degrees celsius 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc single section50.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section-20.00/+20.00 percent single section

**Case Material:**

Metalmetal

**Capacitive Electrode Material:**

Tantalumtantalum

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plasticplastic

**Precious Material And Location:**

Case surface silvercase surface silver

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0