Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-176-7220

## Body Style:

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

2.000 inches

## **Body Diameter:**

0.750 inches

## **Body Length:**

2.125 inches

## Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## Anode Type:

Plain foil

# Impedance At Minimum Operating Tempurature In Ohms:

740.0

#### **Electrical Polarization:**

Polarized

### Capacitance Value Per Section:

20.000 microfarads single section

#### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 50.00 percent single section

#### Case Material:

Metal

Capacitive Electrode Material:

Aluminum

# Dissipation Factor At Reference Tempurature In Percent:

17.0000

# Dc Leakage At Reference Temp:

133.000 microamperes

# **Terminal Surface Treatment:**

Solder

#### **Case Insulation Material:**

Plastic

#### **Test Data Document:**

81349-mil-c62/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

# NSN 5910-00-176-7220

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0