Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-177-6612

# **Body Style:**

W/o mtg facilities, terminal (s) on one end

# **Reliability Indicator:**

Not established

# Body Diameter:

1.312 inches

# **Body Length:**

2.562 inches

### Schematic Diagram Designator:

One terminal common to each section

# Anode Type:

Plain foil

# Impedance At Minimum Operating Tempurature In Ohms:

880.0

# **Electrical Polarization:**

LICCU

# Polarized

Section Quantity:

2

# **Capacitance Value Per Section:**

10.000 microfarads all sections

# Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

350.0 dc all sections

### **Tolerance Range Per Section:**

-10.00 to 50.00 percent 2nd section

### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

### **Dissipation Factor At Reference Tempurature In Percent:**

12.0000

Dc Leakage At Reference Temp:

88.000 microamperes

# **Terminal Surface Treatment:**

Nickel

# **Case Insulation Material:**

Plastic

### **Test Data Document:**

81349-mil-c62/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

3 standard tube base

# NSN 5910-00-177-6612

Electrolytic Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0