NSN 5910-00-180-3145

Quartz Dielectric Variable Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-180-3145
Body Style:
Piston
Overall Length:
1.093 inches
Body Length:
1.031 inches
Overall Diameter:
0.375 inches
Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:
-75.0 to 75.0 single section
Center To Center Distance Between Terminals Parallel To Length:
0.750 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.344 inches
Quality Factor At 25 Deg Celsius:
1000.0
Inclosure Type:
Encased
Mounting Facility Type And Quantity:
mounting racinty rype And Quantity.
2 terminal
2 terminal
2 terminal Nonderated Operating Temp:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead Shelf Life:
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
2 terminal Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead Shelf Life: N/a
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:
Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +8.0 to 12.0 single section Nonderated Voltage Rating And Type: 2600.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 slotted screw Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: