NSN 5910-00-181-3880

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-181-3880 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.810 inches **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.340 inches **Body Length:** 0.470 inches **Overall Diameter:** 0.310 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 750.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches **Capacitance Range In Picofarads:**

+1.0 to 16.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

NSN 5910-00-181-3880

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal T	Type And	Quantity:
------------	----------	-----------

1 turret and 1 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0