Mica Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-184-5722

Not established Body Width: 1.266 inches Body Height: 1.844 inches Body Height: 1.844 inches Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps: 3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: 200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:	Body Width: 1.266 inches	
1.266 inches Body Height: 1.844 inches Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps: 3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: 200.0 to 200.0 single section Plastic Plastic Stheff Life: N/a Unit Of Measure: Pemilitarization: No Fig:	1.266 inches	
Body Height: 1.844 inches Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps: 3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: 200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No		
1.844 inches Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps: 3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:		
Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps: 3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Sheff Life: N/a Lint Of Measure: - Pemilitarization: No Fig:	Body Height:	
3.0 Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: - - Demilitarization: No	1.844 inches	
Unthreaded Mounting Hole Diameter: 0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:	
0.180 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: - Demilitarization: No	3.0	
Schematic Diagram Designator:No common or grounded electrode (s)Capacitance Value Per Section:8000.000 picofarads single sectionNonderated Operating Temp:Unable to decode and 85.0 degrees celsiusTempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:-200.0 to 200.0 single sectionCase Material:PlasticTerminal Type And Quantity:2 threaded studShelf Life:N/aInit Of Measure:Femilitarization:NoFig:	Unthreaded Mounting Hole Diameter:	
No common or grounded electrode (s) Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.180 inches	
Capacitance Value Per Section: 8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	Schematic Diagram Designator:	
8000.000 picofarads single section Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: -200.0 to 200.0 single section Case Material: Plastic Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	No common or grounded electrode (s)	
Nonderated Operating Temp: Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No	Capacitance Value Per Section:	
Unable to decode and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	8000.000 picofarads single section	
Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -200.0 to 200.0 single section Case Material: Plastic Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nonderated Operating Temp:	
-200.0 to 200.0 single section Case Material: Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Unable to decode and 85.0 degrees celsius	
Case Material: Plastic Plastic Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius	;:
Plastic Terminal Type And Quantity: 2 threaded stud 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-200.0 to 200.0 single section	
Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Case Material:	
2 threaded stud Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Plastic	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:	
N/a Unit Of Measure: Demilitarization: No Fiig:	2 threaded stud	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A010b0	Fiig:	
	A010b0	