

View Online at <https://aerobasegroup.com/nsn/5910-00-186-0296>

Body Style:

W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, terminal(s) on one end

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

Between 0.437 inches and 0.437 inches and 0.437 inches and 0.563 inches 0.563 inches 0.563 inches

Body Diameter:

Between 0.984 inches and 1.016 inches

Body Length:

Between 2.937 inches and 3.063 inches

Schematic Diagram Designator:

Electrod (s) grounded to case

Anode Type:

Etched foil

Electrical Polarization:

Polarized

Section Quantity:

3

Capacitance Value Per Section:

50.000 microfarads all sections

Nonderated Operating Temp:

Between -30.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc all sections

Tolerance Range Per Section:

-10.00/+150.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Temperature In Percent:

15.000

Dc Leakage At Reference Temp:

10.000 milliamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0