

View Online at <https://aerobasegroup.com/nsn/5910-00-186-0296>

**Body Style:**

W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

Between 0.437 inches and 0.437 inches and 0.437 inches and 0.563 inches 0.563 inches 0.563 inches

**Body Diameter:**

Between 0.984 inches and 1.016 inches

**Body Length:**

Between 2.937 inches and 3.063 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case

**Anode Type:**

Etched foil

**Electrical Polarization:**

Polarized

**Section Quantity:**

3

**Capacitance Value Per Section:**

50.000 microfarads all sections

**Nonderated Operating Temp:**

Between -30.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

50.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+150.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

15.000

**Dc Leakage At Reference Temp:**

10.000 milliamperes

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0