Air Dielectric Variable Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-186-1578

Overall Length:3.188 inchesShaft Diameter:0.250 inches single shaftShaft Length:1.406 inches single shaftInclosure Type:UninclosedTuning Characteristic:Straight line capacity single sectionAdjustment Device Rotation:180.0 degrees clockwise and 180.0 degrees counterclockwiseMounting Facility Type And Quantity:1 bracketShaft Type:Round single shaftCapacitance Range In Picofarads:+10.0 to 245.0 single sectionAdjustment Device Drive Type And Quantity:1 shaftTerminal Type And Quantity:1 shaftTerminal Type And Quantity:3 tab, solder lugSheft Life:N/aUnit Of Measure:Pemilitarization:NoFig:Augea0	
Shaft Diameter: 0.250 inches single shaft Shaft Length: 1.406 inches single shaft Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Overall Length:
0.250 inches single shaft Shaft Length: 1.406 inches single shaft Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	3.188 inches
Shaft Length: 1.406 inches single shaft Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Shaft Diameter:
1.406 inches single shaft Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: - - Demilitarization: No	0.250 inches single shaft
Inclosure Type: Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Shaft Length:
Uninclosed Tuning Characteristic: Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	1.406 inches single shaft
Tuning Characteristic:Straight line capacity single sectionAdjustment Device Rotation:180.0 degrees clockwise and 180.0 degrees counterclockwiseMounting Facility Type And Quantity:1 bracketShaft Type:Round single shaftCapacitance Range In Picofarads:+10.0 to 245.0 single sectionNonderated Voltage Rating And Type:500.0 ac peak single sectionAdjustment Device Drive Type And Quantity:1 shaftTerminal Type And Quantity:3 tab, solder lugSheff Life:N/aIn Coff Measure:Pemilitarization:NoFig:	Inclosure Type:
Straight line capacity single section Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Uninclosed
Adjustment Device Rotation: 180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Tuning Characteristic:
180.0 degrees clockwise and 180.0 degrees counterclockwise Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Straight line capacity single section
Mounting Facility Type And Quantity: 1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Adjustment Device Rotation:
1 bracket Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	180.0 degrees clockwise and 180.0 degrees counterclockwise
Shaft Type: Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Mounting Facility Type And Quantity:
Round single shaft Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	1 bracket
Capacitance Range In Picofarads: +10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Shaft Type:
+10.0 to 245.0 single section Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Round single shaft
Nonderated Voltage Rating And Type: 500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Fig:	Capacitance Range In Picofarads:
500.0 ac peak single section Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	+10.0 to 245.0 single section
Adjustment Device Drive Type And Quantity: 1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Nonderated Voltage Rating And Type:
1 shaft Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	500.0 ac peak single section
Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Adjustment Device Drive Type And Quantity:
3 tab, solder lug Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	1 shaft
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure:  Demilitarization: No Fiig:	3 tab, solder lug
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A096a0	Fiig:
	A096a0