Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-187-2550

# Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

Body Length:

0.500 inches

Body Width:

0.280 inches

**Body Height:** 

0.125 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

6800.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-200.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-2.00 to 2.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

1000000.0 megohms

# **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

#### **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0