## NSN 5910-00-188-1480

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-188-1480

**Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 3.750 inches **Body Width:** 2.250 inches **Body Height:** 5.125 inches **Center To Center Distance Between Terminals Parallel To Length:** 2.000 inches **Terminal Height From Body:** 2.750 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Inserted tab **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 0.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 standoff, solder stud

**Test Data Document:** 

## NSN 5910-00-188-1480

Paper Dielectric Fixed Capacitor - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-c-25/7e government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0