# NSN 5910-00-188-7507

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-188-7507

## **Body Style:**

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not establishednot establishednot established

## Terminal Length:

1.500 inches 1.500 inches 1.500 inches

## **Body Diameter:**

0.161 inches

#### **Body Length:**

0.575 inches

## **Terminal Diameter:**

0.020 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

### Anode Type:

Solid

### **Electrical Polarization:**

Nonpolarized

### **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

1.100 microfarads single section

## Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

6.0 microamperes

# Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

# **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

## Case Material:

Metal

# **Capacitive Electrode Material:**

Tantalum

# Dissipation Factor At Reference Tempurature In Percent:

2.0000

# Dc Leakage At Reference Temp:

0.600 microamperes

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic

Electrolytic Fixed Capacitor - Page 2 of 2



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0