## NSN 5910-00-189-2933

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-189-2933

| view Offiline at https://acrobasegroup.com/nish/05/10-00-105-2555            |
|--|
| Body Style:  |
| W/mtg tabs/flanges, terminal (s) on one surface                              |
| Reliability Indicator:   |
| Not established  |
| Mounting Slot Width:   |
| Between 0.188 inches and 0.312 inches  |
| Body Length:   |
| 1.812 inches   |
| Body Width:  |
| 1.062 inches   |
| Body Height:   |
| 2.000 inches   |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 0.812 inches   |
| Terminal Height From Body:   |
| 0.500 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.312 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Mounting Facility Type And Quantity:   |
| 2 mounting slots   |
| Features Provided:   |
| Mounting hardware and hermetically sealed case                               |
| Capacitance Value Per Section:   |
| 0.150 microfarads single section   |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 85.0 degrees celsius                       |
| Nonderated Continuous Voltage Rating And Type Per Section:                   |
| 600.0 dc single section  |
| Tolerance Range Per Section:   |
| -10.00 to 10.00 percent single section                                       |
| Case Material:   |
| Metal  |
| Terminal Surface Treatment:  |
| Solder   |
| Terminal Type And Quantity:  |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5910-00-189-2933

Paper Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0