## NSN 5910-00-189-7513

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-189-7513 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.250 inches **Body Diameter:** 0.578 inches **Body Length:** 0.766 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 93.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 25.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 12.5 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 125.0 dc single section **Tolerance Range Per Section:** -15.00 to 30.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Power Factor At Reference Tempurature In Percent:** 18.7000 **Equivalent Series Resistance At Reference Tempurature In Ohms:** Dc Leakage At Reference Temp: 2.000 microamperes **Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-189-7513

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	I if	ρ.
~	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0